

K-Resin KR52

Styrene Butadiene Copolymer (SBC)

TECHNICAL DATASHEET

DESCRIPTION

K-Resin® KR52 makes a clear, stiff, very tough, high gloss film suitable for applications such as candy twist wrap, shrink sleeves and overwrap. K-Resin® KR52 is designed for use in the uniaxial oriented film process for shrink sleeves.

FEATURES

- Excellent Optical Properties
- Good Stiffness
- Excellent Printability
- Up to 80% Shrinkage at 100°C

APPLICATIONS

- Shrink Sleeve Labels
- Multi-layer Films
- Tamper Evident Bands
- Roll-Fed Labels

Property, Test Condition	Standard	Unit	Values
Rheological Properties			
Mechanical Properties			
Elemendorf Tear (MD)	-	g	95
Elemendorf Tear (TD)	-	g	75
Thermal Properties			
Optical Properties			
Other Properties			

The nominal properties herein are typical of the product but do not reflect normal testing variance and therefore should not be used for specification purposes. Values are rounded.

Typical cast film properties with 2% impact polystyrene, 2 mil (0.05 mm) (10 mil cast film oriented/tentered 5:1 in the Transverse Direction).

[Vicat Softening Point] = Injection Molded Specimen.

DISCLAIMER

The aforementioned data shall constitute the agreed contractual quality of the product sold by INEOS Styrolution at the time of passing of risk. INEOS Styrolution does not make any further warranty, representation or guarantee of any kind, express or implied, regarding the suitability of the product for any particular purpose or application and INEOS Styrolution disclaims all liability in connection therewith. The customer himself is required to verify whether or not the product is suitable for the further processing or application intended and whether or not the product complies with the relevant statutory requirements. Unless explicitly and individually otherwise agreed in writing, INEOS Styrolution's sole and exclusive liability with respect to its products is set forth in INEOS Styrolution's General Terms and Conditions for Sale.